

# HP Stitch S500 64-in Printer

The robust, efficient printer for highly demanding dye sub users<sup>1</sup>



\*Product image may differ from actual product

## Enjoy reliable, unattended printing

- Print an entire shift unattended or overnight with the largest media rolls<sup>2</sup> and large ink supplies.
- Get reliable image quality with 2xCMYK printheads and automatic compensation of up to 30% nozzles out.<sup>1</sup>
- Reduce telescoping and manual media adjustments with the tension sensing winder and media advance sensor.
- Rely on colour consistency from printer to printer.<sup>2</sup>

## Optimise your uptime with easy maintenance

- Reduce downtime and service costs. For the first time, you can replace the printheads yourself.<sup>2</sup>
- Stay ready to print outstanding quality, and reduce manual interventions, with automatic maintenance.
- Simplify and control your print operations and maximise uptime with HP Service and HP PrintOS.

## Perfect for fleet environments

- Double your unattended printing capacity without increasing your production space.<sup>2</sup>
- Efficiently manage your fleet, and remotely monitor printer status and ink and substrate use, with HP PrintOS.
- Easily observe the status of your printer—at a glance and from afar—with the highly visible beacon.

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: <http://www.hp.com/learn/ds>

## Messaging Footnotes

- <sup>1</sup> Reliable image quality enabled with 2xCMYK printheads and automatic compensation of up to 30% nozzles out based on internal HP testing, July 2020. Unattended printing enabled by large media rolls and large ink supplies.
- <sup>2</sup> Compared to alternative 64-inch dye-sublimation based textile printers available as of June, 2020. Largest rolls up to 55 kg. The HP Stitch S Printer series provides HP SmartColour tools and a built-in spectrophotometer for colour consistency. Front media loading saves 50% floor space.

For more information, please visit <http://www.hp.com/go/stitchs500>



# Technical specifications

<b>Print</b>	
<b>Print speed</b>	110 m <sup>2</sup> /hr - Max Speed (1-pass); 62 m <sup>2</sup> /hr - Production Fast (2-pass); 43 m <sup>2</sup> /hr - Production Quality (3-pass); 34 m <sup>2</sup> /hr - Quality (4-pass); 22 m <sup>2</sup> /hr - High Quality (6-pass);
<b>Print resolution</b>	Up to 1200 x 1200 dpi
<b>Technology</b>	HP Dye Sub Printing Technologies
<b>Margins (roll)</b>	5 x 5 x 0 x 0 mm (without edge holders)
<b>Ink types</b>	HP Dye Sub Inks
<b>Print Cartridges/Bottle, Number</b>	4 (cyan, magenta, yellow, black)
<b>Print cartridge/bottle volume</b>	3 L, 775 ml
<b>Ink drop</b>	12 pl
<b>Printheads</b>	8 HP Thermal Inkjet (4 cyan/black, 4 magenta/yellow)
<b>Long-term print-to-print repeatability</b>	Average ≤ 1 dE2000, 95% of colours ≤ 1.5 dE2000 <sup>1</sup>
<b>Media</b>	
<b>Applications</b>	Interior decoration; Fashion; Sportswear; Soft signage
<b>Handling</b>	Roll feed, take-up reel, automatic cutter (for transfer media)
<b>Media rolls</b>	1
<b>Roll size</b>	580 to 1625-mm rolls;
<b>Maximum roll weight</b>	55 kg;
<b>Maximum roll diameter</b>	250 mm;
<b>Maximum media width</b>	1625 mm;
<b>Thickness</b>	Up to 0.5 mm;
<b>Media types</b>	Sublimation transfer papers, sublimation polyester fabrics, sublimation film
<b>Connectivity</b>	
<b>Interfaces</b>	Gigabit Ethernet (1000Base-T)
<b>Dimensions (W x D x H)</b>	

<b>Product</b>	2550 x 810 x 1420 mm;
<b>Shipping</b>	2740 x 1070 x 1700 mm;
<b>Weight</b>	
<b>Product</b>	235 kg;
<b>Shipping</b>	431 kg;
<b>Included</b>	
<b>What's in the box</b>	HP Stitch S500 64-in Printer, printer stand, printheads, maintenance cartridge, take-up reel, 2-in adaptor kit, beacon light, ink collector, loading accessory, edge holders, user maintenance kit, waste bottle, quick reference guide, setup poster, documentation software, power cords, HP Ergosoft RIP Color Edition
<b>Environmental ranges</b>	
<b>Operating temperature</b>	15 to 30°C;
<b>Operating humidity</b>	20 to 80% RH (non-condensing) <sup>2</sup>
<b>Acoustics</b>	
<b>Sound pressure</b>	Printing: 55 dB(A) (operating), 38 dB(A) (idle), <16 dB(A) (sleep)
<b>Sound power</b>	Printing: 7.3 B(A) (operating), 5.6 B(A) (idle), <3.5 B(A) (sleep)
<b>Power</b>	
<b>Consumption</b>	1 kW (printing); 80 W (ready); < 2 W (sleep)
<b>Requirements</b>	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); one power cord; 13 A max. Not dual voltage, power supply varies by part number with # Option code identifier.
<b>Certification</b>	
<b>Safety</b>	IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Ukraine (UA); Argentina (IRAM)
<b>Electromagnetic</b>	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC)
<b>Environmental</b>	ENERGY STAR®; WEEE; EU RoHS; China RoHS; RoHS Korea; RoHS India; RoHS Ukraine; RoHS Turkey; REACH; EPEAT; OSHA; CE marking compliant
<b>Warranty</b>	One-year limited hardware warranty

## Ordering information

<b>Product</b>	
2ET73A	HP Stitch S500 64-in Printer
<b>Accessories</b>	
5JX30A	HP Stitch S300/S500 Ink Collector
5QG59A	HP Ergosoft Pro RIP Color Edition
5QG72A	HP Stitch S300/S500 User Maintenance Kit
F0M64A	HP Series 300/500 Edge Holder Kit
T7U74A	HP Series 300/500 Ink Collector Foam Kit
<b>Original HP printing supplies</b>	

2LL53A	HP 624 775-ml Black Stitch Dye Sublimation Ink Cartridge
2LL54A	HP 624 775-ml Cyan Stitch Dye Sublimation Ink Cartridge
2LL55A	HP 624 775-ml Magenta Stitch Dye Sublimation Ink Cartridge
2LL56A	HP 624 775-ml Yellow Stitch Dye Sublimation Ink Cartridge
2LL61A	HP 614 Stitch Dye Sublimation Printhead Cleaning Kit
2LL62A	HP 614 Cyan and Black Stitch Dye Sublimation Printhead
2LL63A	HP 614 Magenta and Yellow Stitch Dye Sublimation Printhead

Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit <https://hp.com/go/OriginalHPInks>

HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit <http://www.hp.com/go/cpc>

## Specification Footnotes

<sup>1</sup> The colour variation inside a printed job has been measured at 6-pass mode on transfer media and also in direct-to-fabric situations within this limit: maximum colour difference (95% of colours) ≤ 1.5 dE2000. Reflective measurements on a 943 colour target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colours may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results. Results are dependent on sublimation process variability.

<sup>2</sup> Papers are hygroscopic materials. They can absorb or lose moisture depending on external humidity conditions. A low level of substrate's moisture and external relative humidity is always recommended when printing on paper based materials. Recommended external relative humidity is between 25% to 50%.

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

March 2025  
ng-en

