

Solutions for plastering, grouting & TSL



Overview

The Rockcreter TSL pump is equipped with a powerful ribbon mixer ensure a homogeneous mix across all products, even with heavy materials such as repair mortars and specialised grouts. The robust design ensures easy handling and ease of maintenance.

- Easy to transport
- Easy to clean
- Simple to operate
- Low maintenance

Applications

- Thin Skinliners
- Grout pumping
- Self levelling screeds
- Plaster spraying
- Filling Joints
- Resurfacing works
- Void Filling
- Slab Jacking
- → Interior/Exterior Finishes



Solutions for plastering, grouting & TSL



Technical Specifications

Dimensions Length : 900mm

Width : 700mm Height : 1200mm Weight : 240kg

Rotor Stator D8 - 2

Pump capacity / output : Up to 1cub m /hour

Aggregate size : Up to 4mm

Pressure : 35 bar pumping pressure Conveying distance : Up to 30m [material dependant]

Drive Options Air drive pump : Air Requirements 4 - 6 bar @ 400cfm

Electric drive pump : 3kW on pump, 0.75kW on mixer

Options : Variable speed

External compressor
External vibrator



Rockcrete Equipment (PTY) LTD 361 Crocker Road Wadeville, Germiston 1428 Phone: +27 11 865 3019

Email: information@rockcrete.co.za

www.rockcrete.co.za